

# BUNN®

## BrewWISE® Dual Soft Heat® DBC Brewer

ITEM#

PROJECT

DATE

### Features

#### BrewWISE® Brewing System

- Brews 18.9 gallons (71.5 litres) of perfect coffee per hour.
- Brews ½, 1, or 1½ gallon (1.9, 3.8 or 5.7 litre) batches.
- Stores individual coffee and flavor profiles using adjustable water volume, bypass percentage, pulse brew, and pre-infusion timing.
- Operate any combination of BrewWISE equipment error-free with wireless brewer-grinder interface via Smart Funnel®.
- Reduce accidents with safety features that decrease hot splashes from funnel, eliminate brewing when funnel or server is not present.
- Troubleshoot all switches and electrical components from the front panel with advanced diagnostic service tools.
- Simplify installation and calibration by creating your own recipe cards and dedicated funnels with the BrewWISE Recipe Writer using your PC (Windows® compatible).
- International electrical configurations available.



#### Model Dual SH DBC with 1.5 gallon SH Servers

(servers sold separately)

Dimensions: 35.8" H x 18" W x 21.2" D  
(90.9cm H x 45.7cm W x 53.8cm D)

For current specification sheets and other information, go to [www.bunn.com](http://www.bunn.com).

### Related Products

**Easy Clear® EQHP-25L**  
Product No. : 39000.0002



**Easy Clear® EQHP-25**  
Product No. : 39000.0005

**Single/Dual Filter Pack**  
Product No. : 20138.0000  
Packed per case: 500  
Dimensions:



5¼" Base x 4¼" Sidewall  
13.3 cm Base x 10.8 cm Sidewall

**BrewWISE® Recipe Writer (BRW)**  
Product No.: 34444.0000




**Recipe Card**  
Product No.: 34447.0000

- Program a recipe to be used on brewer or grinder.



**Ad Card**  
Product No.: 34448.0000

- Program a message to appear on the brewer's display.



**Two Position Drip Tray**  
Product No.: 27150.0000



**SH Server**  
Product No. : 27850.0001



**2SH Stand**  
Product No. : 27875.0000



**MHG**  
Product No.: 35600.0000



**G9-2T DBC**  
Product No.: 33700.0000

#### Model

Dual SH DBC

#### Agency Listing



Patents Apply

9/08

A2.9

## Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Capacity	Cubic Measure	Shipping Weight	Cord Attached
Dual SH DBC	33500.0000	120/240	29.1	2@3300	6800	18.9 gal/hr	13.3 ft <sup>3</sup>	90 lbs.	No
Dual SH DBC†	33500.0006	120/240	29.1	2@3300	6800	18.9 gal/hr.	13.3 ft <sup>3</sup>	90 lbs.	No
Dual SH DBC*	33500.0004	120/240	29.1	2@3300	6800	18.9 gal/hr.	13.3 ft <sup>3</sup>	90 lbs.	No
SH Server(1.5 gal.)	27850.0001	n/a	n/a	n/a	n/a	1.9 gal.	2.4 ft <sup>3</sup>	17 lbs.	n/a
SH Server*(1.5 gal.)	27850.0004	n/a	n/a	n/a	n/a	1.9 gal.	2.4 ft <sup>3</sup>	17 lbs.	n/a
1SH Stand	27825.0000	120	.8	n/a	90	1 SH Server	1.2 ft <sup>3</sup>	13 lbs.	Yes
1SH Stand*	27825.0004	120	.8	n/a	90	1 SH Server	1.2 ft <sup>3</sup>	13 lbs.	Yes
2SH Stand	27875.0000	120	1.5	n/a	180	2 SH Servers	2.1 ft <sup>3</sup>	22 lbs.	Yes
2SH Stand*	27875.0003	120	1.5	n/a	180	2 SH Servers	2.1 ft <sup>3</sup>	22 lbs.	Yes

\* Models have black finish.

† Model has lower faucet.

Note: Soft Heat® Brewers and Servers are boxed and shipped separately.

**Brewing capacity:** based upon incoming water temp of 60°F/15°C (140°F/60°C rise).

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

Electrical: Brewer is 3-wires plus ground service rated 120/240V, single phase, 50/60Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with ¼" male fitting. Tank capacity: 8.4 gallons (31.8 L)

